



Confined Space Covers

Barrier Protection & Signage, All-in-One

All confined spaces are considered to be permit required until a hazard assessment has identified the dangers within



A Permit Required Confined Space:

- + Is an area that is large enough for a worker to enter, but has **limited access for entry & exit** and is not made for human occupancy
- + Has **potential hazards** due to its configuration such as fall hazards or entrapment
- + Has **potential dangers** such as low oxygen, toxic gases, chemical exposures, temperature extremes & more

Confined Spaces can cause serious injury or even death for workers entering the space if they are exposed to the dangers that reside within the space

What OSHA Requires

- Consistently identify the confined spaces in your workplace with signage
- Display required 'Danger' signage to alert workers of the confined spaces & associated dangers
- Prevent unauthorized entry during times when your confined spaces are not being monitored

"Requirements per OSHA's 29CFR 1910.146 Standard for Permit-Required Confined Spaces"



MASTER LOCK CONFINED SPACE COVERS PROVIDE OSHA REQUIRED SIGNAGE AND EFFECTIVELY PREVENT AGAINST UNAUTHORIZED ENTRANCE.

ALL IN ONE, EASY TO USE PRODUCT.



What Are Confined Space Covers?

Master Lock confined space covers are the **best practice solution** for complying with OSHA and protecting your employees from the dangers of confined spaces. They provide required signage as well as an effective barrier to entry, exceeding the OSHA requirements.





When Do I Use Covers?

- Once a confined space entryway has been opened, covers provide required signage needed to alert workers of confined space danger
- + During **long periods between entry operations**, lockable covers provide added security and shield against contamination of the space
- During break periods of active maintenance, ventilated covers provide excellent signage and encourage air flow

3 Models Available in 4 Sizes (Small, Medium, Large & Extra Large)




\$201CSElastic,
non-lockable,
ventilated



S202CSLockable, ventilated



S203CS Lockable, solid



How to Determine Size Needed		
Man-Way Diameter	Size	Suffix
20in – 23in	Small	S
23in – 28in	Medium	M
28in – 32in	Large	L
32in – 39in	X-Large	XL

* Size also depends on flange size

Add size suffix to model number to order. Ex. S202CSXL for X-Large



OSHA Compliant +

Quick, easy & efficient application
Effectively prevents unwanted entry
Withstands extreme environments
Prominently displays 'Danger' Signage
Easy to clean & store

= BEST PRACTICE SOLUTION

Lockable covers should be secured with a different type of lock than what is used for your safety lockout procedures. We recommend using a security lock such as:

- Master Lock 311
 Covered Laminated Padlock
- + American Lock A20 Solid Brass Padlock
- Master Lock 6121
 Weather Tough® Padlock
- Master Lock 975
 Resettable Combination Padlock



For More Information Visit www.masterlocksafety.com/CSC Or call 1-800-604-9258



w w w . m a s t e r l o c k s a f e t y . c o m w w w . m a s t e r l o c k . c o m

Master Lock Company LLC, Milwaukee, WI 53210 U.S.A. | 800-308-9244 Master Lock Canada, Mississauga, Ontario L5L 5Z9 Canada | 800-227-9599 © 2017 Master Lock Company LLC | All Rights Reserved