

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: Master Lock Aerosol Lock Lubricant with PTFE** SKU Description: 2300 and 2300DCLP
- **Article number:** No other identifiers.
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture** Lubricant
- **1.3 Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**  
Synco Chemical Corporation  
24 DaVinci Dr., P.O. Box 405  
Bohemia, NY 11716  
  
Telephone: 631-567-5300
- **1.4 Emergency telephone number:**  
CHEMTREC  
1-800-424-9300 (US/Canada)  
+01 703-527-3887 (International)

### SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**  
The product is not classified as hazardous according to OSHA GHS regulations within the United States.  
The product is not classified as hazardous according to the CLP regulation.

---

- **Information concerning particular hazards for human and environment:**  
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
- **Classification system:**  
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.  
The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.
- **Additional information:**  
There are no other hazards not otherwise classified that have been identified.  
0 percent of the mixture consists of component(s) of unknown toxicity

---

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is not classified as hazardous according to OSHA GHS regulations within the United States.  
This product does not have a classification according to the CLP regulation.
- **Hazard pictograms** Not Regulated
- **Signal word** Not Regulated
- **Hazard statements** Not Regulated

(Contd. on page 2)

# Safety Data Sheet

according to 1272/2008/EC (CLP) and OSHA GHS

Revision: October 22, 2015

Trade name: Master Lock Aerosol Lock Lubricant with PTFE

(Contd. of page 1)

- **Precautionary statements** Not Regulated
- **Additional information:**  
EUH210 Safety data sheet available on request.
- **Hazard description:**
- **WHMIS-symbols:** Not hazardous under WHMIS.
- **NFPA ratings (scale 0 - 4)**



Health = 1  
Fire = 1  
Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



HEALTH 1 Health = 1  
FIRE 1 Fire = 1  
REACTIVITY 0 Reactivity = 0

- **HMIS Long Term Health Hazard Substances**

None of the ingredients are listed.

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

## SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 25322-69-4	Poly(proylene glycol)	Eye Irrit. 2, H319 Aquatic Chronic 3, H412	≤ %2,5
-----------------	-----------------------	---	--------

- **Additional information:**  
For the listed ingredients, the identity and exact percentages are being withheld as a trade secret.  
For the wording of the listed risk phrases refer to section 16.

## SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:**  
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.  
Take affected persons out into the fresh air.

(Contd. on page 3)

## Safety Data Sheet

according to 1272/2008/EC (CLP) and OSHA GHS

Revision: October 22, 2015

**Trade name: Master Lock Aerosol Lock Lubricant with PTFE**

(Contd. of page 2)

- **After inhalation:**  
Supply fresh air; consult doctor in case of complaints.  
Provide oxygen treatment if affected person has difficulty breathing.  
In case of irregular breathing or respiratory arrest provide artificial respiration.
- **After skin contact:**  
Immediately rinse with water.  
If skin irritation is experienced, consult a doctor.
- **After eye contact:**  
Protect unharmed eye.  
Remove contact lenses if worn.  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:**  
Rinse out mouth and then drink plenty of water.  
Do not induce vomiting; call for medical help immediately.  
A person vomiting while laying on their back should be turned onto their side.
- **4.2 Most important symptoms and effects, both acute and delayed**  
Headache  
Breathing difficulty  
Coughing  
Dizziness  
Gastric or intestinal disorders when ingested.  
Nausea in case of ingestion.
- **Hazards**  
Danger of impaired breathing.  
May be harmful if swallowed.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
Medical supervision for at least 48 hours.  
If necessary oxygen respiration treatment.  
Later observation for pneumonia and pulmonary oedema.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
- **For safety reasons unsuitable extinguishing agents:** Water spray
- **5.2 Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters**
- **Protective equipment:**  
Wear self-contained respiratory protective device.  
Wear fully protective suit.
- **Additional information** Cool endangered receptacles with water fog or haze.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Ensure adequate ventilation

(Contd. on page 4)

## Safety Data Sheet

according to 1272/2008/EC (CLP) and OSHA GHS

Revision: October 22, 2015

**Trade name: Master Lock Aerosol Lock Lubricant with PTFE**

(Contd. of page 3)

Wear protective equipment. Keep unprotected persons away.  
Particular danger of slipping on leaked/spilled product.  
For large spills, use respiratory protective device against the effects of fumes/dust/aerosol.

- **6.2 Environmental precautions:**

Do not allow to enter sewers/ surface or ground water.  
Prevent from spreading (e.g. by damming-in or oil barriers).

- **6.3 Methods and material for containment and cleaning up:**

Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).  
Remove from the water surface (e.g. skim or suck off).  
Dispose contaminated material as waste according to item 13.  
Send for recovery or disposal in suitable receptacles.

- **6.4 Reference to other sections**

See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**

Prevent formation of aerosols.  
Use only in well ventilated areas.  
Avoid splashes or spray in enclosed areas.

- **Information about fire - and explosion protection:** No special measures required.

- **7.2 Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:**

Provide ventilation for receptacles.  
Avoid storage near extreme heat, ignition sources or open flame.

- **Information about storage in one common storage facility:**

Store away from foodstuffs.  
Store away from oxidising agents.

- **Further information about storage conditions:** Store in cool, dry conditions in well sealed receptacles.

- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- **DNELs** No further relevant information available.

- **PNECs** No further relevant information available.

- **Additional information:** The lists valid during the making were used as basis.

(Contd. on page 5)

## Safety Data Sheet

according to 1272/2008/EC (CLP) and OSHA GHS

Revision: October 22, 2015

Trade name: Master Lock Aerosol Lock Lubricant with PTFE

(Contd. of page 4)

- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
The usual precautionary measures are to be adhered to when handling chemicals.  
Keep away from foodstuffs, beverages and feed.  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the eyes and skin.
- **Respiratory protection:**  
Not required under normal conditions of use.  
Use suitable respiratory protective device when aerosol or mist is formed.
- **Protection of hands:**



Protective gloves

- **Material of gloves**  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**  
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Safety glasses

- **Body protection:**  
Not required under normal conditions of use.  
Protection may be required for spills.
- **Limitation and supervision of exposure into the environment** Avoid release to the environment.
- **Risk management measures**  
See Section 7 for additional information.  
No further relevant information available.

### SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

Form:	Liquid
Colour:	Colourless
Odour:	Mild
Odour threshold:	Not determined.

(Contd. on page 6)

## Safety Data Sheet

according to 1272/2008/EC (CLP) and OSHA GHS

Revision: October 22, 2015

Trade name: Master Lock Aerosol Lock Lubricant with PTFE

(Contd. of page 5)

- pH-value at 20 °C (68 °F): 7
- Change in condition
  - Melting point/Melting range: Not Determined.
  - Boiling point/Boiling range: Undetermined.
- Flash point: 220 °C (428 °F)
- Flammability (solid, gaseous): Not applicable.
- Auto/Self-ignition temperature: Not determined.
- Decomposition temperature: Not determined.
- Self-igniting: Product is not self-igniting.
- Danger of explosion: Product does not present an explosion hazard.
- Explosion limits:
  - Lower: Not determined.
  - Upper: Not determined.
- Vapour pressure: Not determined.
- Density at 20 °C (68 °F): 0,87 g/cm<sup>3</sup> (7,26 lbs/gal)
- Relative density: Not determined.
- Vapour density: Not determined.
- Evaporation rate: Not determined.
- Solubility in / Miscibility with water: Not miscible or difficult to mix.
- Partition coefficient (n-octanol/water): Not determined.
- Viscosity:
  - Dynamic: 130 cP
  - Kinematic: 140 cSt
- 9.2 Other information: No further relevant information available.

### SECTION 10: Stability and reactivity

- 10.1 Reactivity
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used and stored according to specifications.
- 10.3 Possibility of hazardous reactions: Reacts with oxidising agents. Toxic fumes may be released if heated above the decomposition point.
- 10.4 Conditions to avoid: Store away from oxidising agents.
- 10.5 Incompatible materials: Oxidizing agents
- 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide  
Possible in traces:

(Contd. on page 7)

## Safety Data Sheet

according to 1272/2008/EC (CLP) and OSHA GHS

Revision: October 22, 2015

**Trade name: Master Lock Aerosol Lock Lubricant with PTFE**

(Contd. of page 6)

Danger of forming toxic pyrolysis products.  
Hydrogen fluoride  
Fluorocarbons  
Danger of toxic fluorine based pyrolysis products.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values relevant for classification:** None.
- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitisation:** No sensitising effects known.
- **Subacute to chronic toxicity:** No further relevant information available.
- **Additional toxicological information:**  
The product is not subject to classification according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version.  
When used and handled according to specifications, the product does not have any harmful effects to our experience and the information provided to us.
- **Acute effects (acute toxicity, irritation and corrosivity):** May be harmful if swallowed.
- **Repeated dose toxicity:** May cause damage to organs through prolonged or repeated exposure.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction):** None.

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

(Contd. on page 8)

## Safety Data Sheet

according to 1272/2008/EC (CLP) and OSHA GHS

Revision: October 22, 2015

Trade name: Master Lock Aerosol Lock Lubricant with PTFE

(Contd. of page 7)

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**

- **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

- **Uncleaned packaging:**

- **Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

- **14.1 UN-Number**

- DOT, ADR, ADN, IMDG, IATA Not Regulated

- **14.2 UN proper shipping name**

- DOT, ADR, ADN, IMDG, IATA Not Regulated

- **14.3 Transport hazard class(es)**

- DOT, ADR, ADN, IMDG, IATA

- Class Not Regulated

- **14.4 Packing group**

- DOT, ADR, IMDG, IATA Not Regulated

- **14.5 Environmental hazards:**

- Marine pollutant: No

- **14.6 Special precautions for user** Not applicable.

- **14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

- UN "Model Regulation": -

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- United States (USA)

- SARA

- **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

- **Section 313 (Specific toxic chemical listings):**

None of the ingredients are listed.

- **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

(Contd. on page 9)



## Safety Data Sheet

according to 1272/2008/EC (CLP) and OSHA GHS

Revision: October 22, 2015

Trade name: Master Lock Aerosol Lock Lubricant with PTFE

(Contd. of page 8)

- **Proposition 65 (California):**

- **Chemicals known to cause cancer:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

- **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

- **Carcinogenic Categories**

- **EPA (Environmental Protection Agency)**

None of the ingredients are listed.

- **IARC (International Agency for Research on Cancer)**

9002-84-0 | Polytetrafluoroethylene

3

- **TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients are listed.

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients are listed.

- **Canada**

- **Canadian Domestic Substances List (DSL)**

All ingredients are listed.

- **Canadian Ingredient Disclosure list (limit 0.1%)**

None of the ingredients are listed.

- **Canadian Ingredient Disclosure list (limit 1%)**

None of the ingredients are listed.

- **Other regulations, limitations and prohibitive regulations**

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

- **Substances of very high concern (SVHC) according to REACH, Article 57**

None of the ingredients are listed.

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.

(Contd. on page 10)

# Safety Data Sheet

according to 1272/2008/EC (CLP) and OSHA GHS

Revision: October 22, 2015

**Trade name: Master Lock Aerosol Lock Lubricant with PTFE**

(Contd. of page 9)

H412 Harmful to aquatic life with long lasting effects.

**· Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
DOT: US Department of Transportation  
IATA: International Air Transport Association  
ACGIH: American Conference of Governmental Industrial Hygienists  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
NFPA: National Fire Protection Association (USA)  
HMIS: Hazardous Materials Identification System (USA)  
WHMIS: Workplace Hazardous Materials Information System (Canada)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2  
Asp. Tox. 1: Aspiration hazard, Hazard Category 1  
Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

**· Sources**

SDS Prepared by:  
Environmental Protection Department