



Hover over image to zoom

MODEL NO. 406MKW417GRN

Green Dielectric Zenex™ Thermoplastic Safety Padlock, 1-1/2in (38mm) Wide with 1-1/2in (38mm) Tall Nylon Shackle, Master Keyed W417 Cylinder

BEST USED FOR



Electrical Lockout



Safety Lockout/Tagout

OVERVIEW & FEATURES

Product Features

- 406 Dielectric Thermoplastic Safety Padlock
- Plastic shackle helps prevent electrocution and arc flashing, also prevents electrical current from shackle to key
- All components are non-sparking and non-magnetic - plastic, copper, brass
- 1-1/2in (38mm) wide, 1-3/4in (45mm) tall, Thermoplastic green body, plastic shackle with 1-1/2in (38mm) clearance
- Designed exclusively for lockout tagout applications
- Durable, lightweight, non-conductive Thermoplastic lock body
- Compliance with "One Employee, One Lock, One Key" directive
- Key retaining - ensures that padlock is not left unlocked
- Master keyed 6-pin tumbler cylinder
- Commercial Packaging, Shelf Pack Qty 6, Master Carton Qty 36

Product Details

The Master Lock No. 406MK417GRN Dielectric Thermoplastic Safety PadlockMaster keyed - a master key opens all the locks in the system although each lock has its own unique key – features a 1-1/2in (38mm) wide Zenex™ Thermoplastic green body and a 1-1/2in (38mm) tall, 1/4in (6mm) diameter plastic shackle to help prevent electrocution and arc flashing and to prevent electrical current from shackle to key. All components are non-sparking and non-magnetic. Designed exclusively for Lockout/Tagout applications, the durable, lightweight material is easy to carry and padlock has key retaining cylinder to ensure the padlock is not left unlocked.

PRODUCT SPECIFICATIONS

Product Number	406MKW417GRN
Description	Master Keyed, Commercial Boxed Packaging
Shelf Pack Qty	6
Master Carton Qty	36
Body Width	1-1/2in (38mm)
Shackle Dimensions	A: 1/4in (6mm) B: 1-1/2in (38mm) C: 25/32in (20mm)

